

SUPERIOR SYNTHETIC ATF

Automatic Transmission Fluid

SUPERIOR SYNTHETIC ATF is a long-life product that will keep transmission components free of carbon deposits and varnish, ensuring long term durability. The fully synthetic polyalphaolefin (PAO) oil is naturally resistant to oxidization at high temperatures, making it ideal for use in demanding conditions encountered by modern heavy-duty transmissions.

Meets the following requirements:

- Allison TES-295 & TES-468
- MB 236.91
- Voith Turbo Diwa Service Bulletins 013 & 118 – Extended Drain
- Voith Turbo H55.6336.xx
- ZF TE-ML 04D & 14C & 16M & 20C & 25C & 165
- MAN 339 Typ V2 & Typ Z12 & Typ Z3

Keep sealed containers out of direct sunlight and at temperatures between 32°F (0°C) and 100°F (40°C). We recommend using the product within two years of opening the container.

BENEFITS:

- Smooth gear shifting
- Extended drain intervals
- Outstanding film strength and anti-wear properties
- Excellent low temperature fluidity
- Compatible with mineral oil-based ATF's

APPLICATIONS:

Suitable for use in modern high-performance trucks, buses, utility vehicles, vans and other equipment requiring performance levels TES-295 (Allison) or 236.91 (MB).

CHARACTERISTICS		
ASTM D-445	Kinematic Viscosity cSt @ 40°C cSt @ 100°C	39 7.3
ASTM D-2270	Viscosity Index	168
ASTM D-97	Pour Point, °F (°C)	-65 (-54)
ASTM D-92	Flash Point, °F (°C) (Cleveland Open Cup)	455 (235)
ASTM D-1298	Specific Gravity	0.85
	Color	Red

The above are typical values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING:

Totes	Drums	Kegs	Pails
-------	-------	------	-------



Rev. June 20, 2022

Brazil: 55 11 2164.3999. USA: 832-491-8873

www.unotechinternational.com
commercial@unotech.com.br